

LM19-L100

19" SXGA LCD Monitor



Features:

- \cdot Industrial level DID LCD panel, suitable for extensive 7×24 continuous works
- · High fidelity digital processing, brilliant and vivid video
- · Built in stereo speakers and audio amplifier
- · HDMI audio support & 3.5mm analog audio inputs automatically track video source selection
- \cdot Suitable for every Video Surveillance and Security application: displays HDMI digital plus VGA, BNC analog inputs













Technical Specification		
Model		
Model	LM19-L100	
System		
Diagonal	19"(5:4)	
Resolution	1280×1024	
Backlight	LED	
Brightness/Luminance (Standard)	250 cd/ m²	
Contrast	1000:1	
Angle of view	178°/178° (vertical/horizontal)	
Response time	5ms	
Signals		

standard VGA(D-Sub)×1, HDMI×1, BNC×1, Audio×1 optional Standard Built in speakers

optional

General

Consumption (Standard)	≤20W
Consumption (Standby)	≤0.5W

Power Supply	AC100~240V (+/-10%),50/60 Hz
Weight	3.88kg(with base)
Dimensions(no base)	418.40x365.10x60.60mm
Work Environment	Temperature:0 C~40 C
work Environment	Humidity:10%~85%

Accessory

Standard	VGA cable, power cable, Pedestal
Optional	hanging bracket

Essential Security Series | LM19-L100



